

#### Safety Data Sheet

According to OSHA 29 CFR 1910.1200

Revision date: 4/23/2019 Supersedes: 8/30/2018 Version: 3.00

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture Product name : Cid 2000 Pro Product code : H45

Product group : Cleaning product.

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

· Professional use Main use category

Use of the substance/mixture : See product bulletin for detailed information

#### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Supplier

CID LINES NV Best Veterinary Solutions, Inc.

Waterpoortstraat, 2 1716 Detroit St B-8900 leper - Belgique P.O. Box 370

T + 32 57 21 78 77 - F +32 57 21 78 79 IA 50075 Ellsworth - United States of America

sds@cidlines.com - http://www.cidlines.com T 888-378-4045

https://www.bestvetsolutions.com/

#### 1.4. Emergency telephone number

···· =····· J····· J····· J····· J···· J··· J··				
Country	Organization/Company	Address	Emergency number	Comment
Canada	CANUTEC Country Organization/Company Address Emergency number Comment		(613) 996-6666	
USA	American Association of Poison Control Centers		1-800-222-1222	

Importer

#### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

#### Labelling according to OSHA 29 CFR 1910.1200

Organic Peroxide Category D H242 Acute toxicity (oral) Category 4 H302 Acute toxicity (inhalation) Category 4 H332 Skin corrosion/irritation Category 1A H314 Specific target organ toxicity (single exposure) Category 3 H335 Hazardous to the aquatic environment - Chronic Hazard Category 1 H410

Full text of H statements : see section 16

#### Adverse physicochemical, human health and environmental effects

No additional information available

#### 2.2. Label elements

#### Labelling according to OSHA 29 CFR 1910.1200

Hazard pictograms (CLP)









GHS02

GHS05

GHS07

GHS09

Signal word (CLP) : Danger

Hazard statements (CLP) : H242 - Heating may cause a fire.

H302+H332 - Harmful if swallowed or if inhaled. H314 - Causes severe skin burns and eye damage.

H335 - May cause respiratory irritation.

H410 - Very toxic to aquatic life with long lasting effects.

#### Safety Data Sheet

According to OSHA 29 CFR 1910.1200

Precautionary statements (CLP) : P280 - Wear protective gloves/protective clothing/eye protection/face protection.

> P260 - Do not breathe dust/fume/gas/mist/vapors/spray. P221 - Take any precaution to avoid mixing with combustibles.

P304+P340 - IF INHALED Remove to fresh air and keep at rest in a position comfortable for breathing. Immediately call a poison center or doctor/physician. Specific treatment is

P301+P330+P331+P310+P321 - IF SWALLOWED Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor/physician. Specific treatment. P303+P361+P353 - IF ON SKIN (or hair)Remove/Take off immediately all contaminated

clothing.Rinse skin with water/shower.

#### 2.3. Other hazards

No additional information available

#### **SECTION 3: Composition/Information on ingredients**

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrogen peroxide	(CAS-No.) 7722-84-1 (EC-No.) 231-765-0 (EC Index-No.) 8-003-00-9 (REACH-no) 01-2119485845-22	15 - 30	Ox. Liq. 1, H271 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Skin Corr. 1A, H314 STOT SE 3, H335 Aquatic Chronic 3, H412
Peracetic acid	(CAS-No.) 79-21-0 (EC-No.) 201-186-8 (EC Index-No.) 607-094-00-8 (REACH-no) 01-2119531330-56	5 - 15	Flam. Liq. 3, H226 Org. Perox. D, H242 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Corr. 1A, H314 STOT SE 3, H335 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Acetic acid	(CAS-No.) 64-19-7 (EC-No.) 200-580-7 (EC Index-No.) 607-002-00-6 (REACH-no) 01-2119475328-30	5 - 15	Flam. Liq. 3, H226 Skin Corr. 1A, H314

Full text of H-phrases: see section 16

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

First-aid measures after inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Seek medical attention immediately

First-aid measures after skin contact

: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Seek medical advice (show the label where possible).

First-aid measures after eye contact

nse immediately with plenty of water. Seek medical attention immediately.

First-aid measures after ingestion

: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor/physician.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation

: Inhalation of vapor can cause breathing difficulties. Cough. Sore throat.

Symptoms/effects after skin contact Symptoms/effects after eye contact

: Redness, pain. Causes severe skin burns and eye damage.

: Redness, pain. Blurred vision. Tears. Serious damage to eyes.

Symptoms/effects after ingestion

: Burning sensation. Cough. Cramps. May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract. Swallowing a small quantity of this material will

result in serious health hazard.

#### 4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

#### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

Suitable extinguishing media : All extinguishing media allowed.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard : May cause fire. Oxidizing

4/23/2019 (Version: 3.00) US-OSHA - en 2/12

#### Safety Data Sheet

According to OSHA 29 CFR 1910.1200

#### 5.3. Advice for firefighters

Precautionary measures fire : Wear fire/flame resistant/retardant clothing. Eliminate all ignition sources if safe to do so.

Firefighting instructions : Use water spray or fog for cooling exposed containers.

Protection during firefighting : Exercise caution when fighting any chemical fire. Do not enter fire area without proper

protective equipment, including respiratory protection. Wear fire/flame resistant/retardant

clothing. Heat resistant gloves.

Other information : On exposure to high temperature, may decompose, releasing toxic gases.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Spill should be handled by trained cleaning personnel properly equipped with respiratory General measures and eye protection. Stop leak if safe to do so. Prevent from entering sewers, basements

and workpits, or any place where its accumulation can be dangerous.

#### 6.1.1. For non-emergency personnel

No additional information available

#### 6.1.2. For emergency responders

No additional information available

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

For containment : Stop leak, if possible without risk. Collect spillage. Use suitable disposal containers.

: Clean up any spills as soon as possible, using an absorbent material to collect it. Methods for cleaning up

#### 6.4. Reference to other sections

No additional information available

#### **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Precautions for safe handling : When handling product, avoid contact with skin and eyes. Wear personal protective equipment. Do not breathe vapor/aerosol. Provide good ventilation in process area to

prevent formation of vapor.

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or

smoking and when leaving work. Handle in accordance with good industrial hygiene and safety procedures.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions Store in dry, cool, well-ventilated area. Provide local exhaust or general room ventilation to

minimize dust and/or vapour concentrations. Keep container closed when not in use.

Minimize exposure to air and light.

#### 7.3. Specific end use(s)

No additional information available

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

Acetic acid (64-19-7)		
Germany	TRGS 910 Acceptable concentration notes	
USA - ACGIH	ACGIH TWA (mg/m³)	25 mg/m³
USA - ACGIH	ACGIH TWA (ppm)	10 ppm
USA - ACGIH	ACGIH STEL (mg/m³)	37 mg/m³
USA - ACGIH	ACGIH STEL (ppm)	15 ppm

Hydrogen peroxide (7722-84-1)		
Germany	TRGS 910 Acceptable concentration notes	
USA - ACGIH	ACGIH TWA (mg/m³)	1.4 mg/m³
USA - ACGIH	ACGIH TWA (ppm)	1 ppm

#### Peracetic acid (79-21-0)

DNEL/DMEL (Workers)		
Acute - systemic effects, inhalation	0.6 mg/m³	
Acute - local effects, dermal	0.12 % in mixture	

# Safety Data Sheet According to OSHA 29 CFR 1910.1200

Peracetic acid (79-21-0)	
Acute - local effects, inhalation	0.6 mg/m³
Long-term - systemic effects, inhalation	0.6 mg/m³
Long-term - local effects, inhalation	0.6 mg/m³
DNEL/DMEL (General population)	
Acute - systemic effects, inhalation	0.6 mg/m³
Acute - local effects, dermal	0.12 % in mixture
Acute - local effects, inhalation	0.3 mg/m³
Long-term - systemic effects, inhalation	0.6 mg/m³
Long-term - local effects, inhalation	0.6 mg/m³
PNEC (Water)	
PNEC aqua (freshwater)	0.000224 mg/l Assessment factor: 10
PNEC (Sediment)	
PNEC sediment (freshwater)	0.00018 mg/kg dwt
PNEC (Soil)	
PNEC soil	0.32 mg/kg dwt Assessment factor: 1000
PNEC (STP)	
PNEC sewage treatment plant	0.051 mg/l Assessment factor: 100
Acetic acid (64-19-7)	
DNEL/DMEL (Workers)	
Acute - local effects, inhalation	25 mg/m³
Long-term - local effects, inhalation	25 mg/m³
DNEL/DMEL (General population)	
Acute - local effects, inhalation	25 mg/m³
Long-term - local effects, inhalation	25 mg/m³
PNEC (Water)	
PNEC aqua (freshwater)	3.058 mg/l Assessment factor: 100
PNEC aqua (marine water)	0.3058 mg/l Assessment factor: 100
PNEC aqua (intermittent, freshwater)	30.58 mg/l Assessment factor: 10
PNEC (Sediment)	
PNEC sediment (freshwater)	11.36 mg/kg dwt
PNEC sediment (marine water)	1.136 mg/kg dwt
PNEC (Soil)	
PNEC soil	0.47 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	85 mg/l Assessment factor: 10
Hydrogen peroxide (7722-84-1)	
DNEL/DMEL (Workers)	
Acute - local effects, inhalation	3 mg/m³
Long-term - local effects, inhalation	1.4 mg/m³
DNEL/DMEL (General population)	
Acute - local effects, inhalation	1.93 mg/m³
Long-term - local effects, inhalation	0.21 mg/m³
PNEC (Water)	
PNEC aqua (freshwater)	0.0126 mg/l Assessment factor: 50
1/23/2010 (Version: 3.00)	11S_OSHA - en //12

#### Safety Data Sheet

According to OSHA 29 CFR 1910.1200

Hydrogen peroxide (7722-84-1)		
PNEC aqua (marine water)	0.0126 mg/l Assessment factor: 50	
PNEC aqua (intermittent, freshwater)	0.0138 mg/l Assessment factor: 100	
PNEC (Sediment)		
PNEC sediment (freshwater)	0.047 mg/kg dwt	
PNEC sediment (marine water)	0.047 mg/kg dwt	
PNEC (Soil)		
PNEC soil	0.0023 mg/kg dwt	
PNEC (STP)		
PNEC sewage treatment plant	4.66 mg/l Assessment factor: 100	
3.2 Exposure controls		

#### Appropriate engineering controls:

Local exhaust and general ventilation must be adequate to meet exposure standards.

#### Personal protective equipment:

Materials for protec	tive clothing:						
Condition		Material		Standard	Standard		
Good resistance:					EN14605:	EN14605:2005+A1:2009	
Hand protection:							
Wear suitable gloves	resistant to ch	nemical pene	tration				
Туре	Material		Permeation	Thickness (mm)	Permeation	on	Standard
Reusable gloves	Polyvinylc (PVC)	hloride	6 (> 480 minutes)	0.5	2 (< 1.5)		EN ISO 374
Eye protection:							
Chemical goggles or	face shield wit	th safety glas	ses				
Type Use		Characteristics		Standard			
Safety glasses, Safety goggles, Face shield  Droplet			Clear, Plastic.		EN 166		
Skin and body prote	ection:						
Wear suitable protect	tive clothing						
Туре				Standard			

Туре	Standard
	EN14605:2005+A1:2009

#### Respiratory protection:

Appropriate dust or mist respirator should be used if airborne particles are generated when handling this material

Device	Filter type	Condition	Standard
Full face mask	ABEK, Type P2	Protection for Liquid particles, Vapour protection, Long term exposure	EN 14387

#### Personal protective equipment symbol(s):









#### Other information:

When using do not eat, drink or smoke. Provide local exhaust or general room ventilation.

#### Safety Data Sheet

According to OSHA 29 CFR 1910.1200

#### **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

Physical state: LiquidAppearance: Clear.Color: Colourless.Odor: Pungent.

Odor threshold : No data available

pH : ≈ 3.5 (1%)

Relative evaporation rate (butyl acetate=1) : No data available

Melting point : - 30 °C

Freezing point : No data available

Boiling point :  $118 \,^{\circ}\text{C}$ Flash point :  $100 \,^{\circ}\text{C}$ 

Auto-ignition temperature : No data available

Decomposition temperature : >= 60 °C

Flammability (solid, gas) : No data available

Vapor pressure : 27 hPa

Relative vapor density at 20 °C : No data available : No data available Relative density Specific gravity / density : ≈ 1.11 kg/l Solubility : Water: 100 % Log Pow : No data available Viscosity, kinematic : No data available : No data available Viscosity, dynamic Explosive properties : No data available : No data available Oxidizing properties : No data available **Explosion limits** 

#### 9.2. Other information

No additional information available

#### **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Reacts violently with: combustibles.

#### 10.2. Chemical stability

No additional information available

#### 10.3. Possibility of hazardous reactions

None under normal conditions.

#### 10.4. Conditions to avoid

heat.

#### 10.5. Incompatible materials

Avoid contact with: acids. Alkaline mixture. Reducing agents. metals. Organic compounds.

#### 10.6. Hazardous decomposition products

May release : Oxygen.

## **SECTION 11: Toxicological information**

#### 11.1. Information on toxicological effects

Acute toxicity (oral) : Harmful if swallowed.

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Harmful if inhaled.

ATE CLP (oral)	500 mg/kg body weight
ATE CLP (gases)	4500 ppmV/4h
ATE CLP (vapors)	11 mg/l/4h
ATE CLP (dust, mist)	1.5 mg/l/4h

Peracetic acid (79-21-0)	
LD50 dermal rabbit	1147 mg/kg (5%, PAA mixture)
LC50 inhalation rat (mg/l)	4h 4080 mg/m³ Aerosol, (5% PAA mixture)

#### Safety Data Sheet

According to OSHA 29 CFR 1910.1200

Acetic acid (64-19-7)	
LD50 oral rat	3310 mg/kg

Hydrogen peroxide (7722-84-1)	
LD50 oral rat	1193 - 1270 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 0.17 mg/l/4h

Skin corrosion/irritation : Causes severe skin burns and eye damage.

pH: ≈ 3.5 (1%)

Serious eye damage/irritation : Eye damage, category 1, implicit

pH: ≈ 3.5 (1%) : Not classified

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified

Specific target organ toxicity – single exposure : May cause respiratory irritation.

Cid 2000 Pro	
LOAEL (oral,rat)	ca. 950 mg/kg body weight
LOAEL (dermal,rat/rabbit)	> 12000 mg/kg body weight

Specific target organ toxicity – repeated exposure : Not classified Aspiration hazard : Not classified

#### **SECTION 12: Ecological information**

#### 12.1. Toxicity

Aquatic acute : Not classified

Aquatic chronic : Very toxic to aquatic life with long lasting effects.

Cid 2000 Pro	
LC50 fish 1 (50-96h) 25 mg/l ca.	
LC50 other aquatic organisms 1	(50-72h) 12 mg/l ca.
EC50 Daphnia 1	(48h) 10 mg/l ca.

Acetic acid (64-19-7)	
LC50 fish 1	> 300 mg/l
EC50 Daphnia 1	> 300 mg/l
EC50 other aquatic organisms 1	> 300 mg/l
ErC50 (algae)	> 300 mg/l

Hydrogen peroxide (7722-84-1)	
LC50 fish 1	37.4 mg/l 96h
EC50 Daphnia 1	7.7 mg/l 24h
12.2. Persistence and degradability	
Cid 2000 Pro	
Persistence and degradability	Biodegradable.
12.3. Bioaccumulative potential	
Cid 2000 Pro	
Bioaccumulative potential	No indication of bioaccumulation potential.

#### Safety Data Sheet

According to OSHA 29 CFR 1910.1200

Peracetic acid (79-21-0)	
Log Kow	-0.26

Acetic acid (64-19-7)	
Log Kow	-0.17

Hydrogen peroxide (7722-84-1)	
Log Pow	-1.57

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Results of PBT and vPvB assessment

No additional information available

#### 12.6. Other adverse effects

No additional information available

#### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Regional legislation (waste)

: Do not empty into drains, dispose of this material and its container at hazardous or special

waste collection point.

Waste treatment methods : Dispose of this material and its container at hazardous or special waste collection point. Hazardous waste due to toxicity. Avoid release to the environment. Dispose in a safe

manner in accordance with local/national regulations.

Sewage disposal recommendations
Product/Packaging disposal recommendations

: Disposal must be done according to official regulations.: When totally empty, containers are recyclable like any other packing. Dispose in a safe

manner in accordance with local/national regulations. Avoid release to the environment.

Ecology - waste materials

: Avoid release to the environment. Hazardous waste due to toxicity.

#### **SECTION 14: Transport information**

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

 UN-No. (ADR)
 : UN 3149

 UN-No. (IMDG)
 : UN 3149

 UN-No. (IATA)
 : UN 3149

 UN-No. (RID)
 : UN 3149

14.2. UN proper shipping name

Proper Shipping Name (ADR) : HYDROGEN PEROXIDE AND PEROXYACETIC ACID MIXTURE STABILIZED
Proper Shipping Name (IMDG) : HYDROGEN PEROXIDE AND PEROXYACETIC ACID MIXTURE STABILIZED

Proper Shipping Name (IATA) : Hydrogen peroxide and peroxyacetic acid mixture stabilized

Proper Shipping Name (ADN) : HYDROGEN PEROXIDE AND PEROXYACETIC ACID MIXTURE STABILIZED
Proper Shipping Name (RID) : HYDROGEN PEROXIDE AND PEROXYACETIC ACID MIXTURE STABILIZED

Transport document description (ADR) : UN 3149 HYDROGEN PEROXIDE AND PEROXYACETIC ACID MIXTURE STABILIZED,

5.1 (8), II, (E), ENVIRONMENTALLY HAZARDOUS

Transport document description (IMDG) : UN 3149 HYDROGEN PEROXIDE AND PEROXYACETIC ACID MIXTURE STABILIZED,

5.1 (8), II, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS

Transport document description (IATA) : UN 3149 Hydrogen peroxide and peroxyacetic acid mixture stabilized, 5.1, II,

ENVIRONMENTALLY HAZARDOUS

Transport document description (ADN) : UN 3149 HYDROGEN PEROXIDE AND PEROXYACETIC ACID MIXTURE STABILIZED,

5.1 (8), II, ENVIRONMENTALLY HAZARDOUS

Transport document description (RID) : UN 3149 HYDROGEN PEROXIDE AND PEROXYACETIC ACID MIXTURE STABILIZED,

5.1 (8), II, ENVIRONMENTALLY HAZARDOUS

#### 14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : 5.1 (8) Hazard labels (ADR) : 5.1, 8

4/23/2019 (Version: 3.00) US-OSHA - en 8/12

#### Safety Data Sheet

According to OSHA 29 CFR 1910.1200





#### **IMDG**

Transport hazard class(es) (IMDG) : 5.1 (8) Hazard labels (IMDG) : 5.1, 8



#### IATA

Transport hazard class(es) (IATA) : 5.1 (8) Hazard labels (IATA) : 5.1, 8



#### **ADN**

: 5.1 (8) Transport hazard class(es) (ADN) Hazard labels (ADN) : 5.1, 8



#### RID

Transport hazard class(es) (RID) : 5.1 (8) : 5.1, 8 Hazard labels (RID)



#### 14.4. Packing group

Packing group (ADR) : II : 11 Packing group (IMDG) : 11 Packing group (IATA) Packing group (ADN) : 11 : 11 Packing group (RID)

#### 14.5. Environmental hazards

Dangerous for the environment : Yes Marine pollutant : Yes

Other information : Clean up even minor leaks or spills, if possible, without unnecessary risk

#### 14.6. Special precautions for user

Special transport precautions : Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency, No naked flames, sparks, and do not smoke, Keep public away from danger area, NOTIFY POLICE AND FIRE BRIGADE

**IMMEDIATELY** 

#### **Overland transport**

Classification code (ADR) : OC1 Special provision (ADR) : 196, 553 Limited quantities (ADR) : 11 Excepted quantities (ADR) : E2

#### Safety Data Sheet

According to OSHA 29 CFR 1910.1200

Packing instructions (ADR) : P504, IBC02
Special packing provisions (ADR) : PP10, B5
Mixed packing provisions (ADR) : MP15
Portable tank and bulk container instructions : T7

(ADR)

Portable tank and bulk container special provisions

(ADR)

: TP2, TP6, TP24

Tank code (ADR) : L4BV(+)

Tank special provisions (ADR) : TU3, TC2, TE8, TE11, TT1

Vehicle for tank carriage : AT
Transport category (ADR) : 2
Special provisions for carriage - Loading, : CV24

unloading and handling (ADR)

Hazard identification number (Kemler No.) : 58

Orange plates :

58 3149

Tunnel restriction code (ADR) : E

Transport by sea

Special provision (IMDG) : 196 Limited quantities (IMDG) : 1 L Excepted quantities (IMDG) : E2 : P504 Packing instructions (IMDG) : PP10 Packing provisions (IMDG) IBC packing instructions (IMDG) : IBC02 IBC special provisions (IMDG) : B5 Tank instructions (IMDG) : T7

Tank special provisions (IMDG) : TP2, TP6, TP24

EmS-No. (Fire): F-HEmS-No. (Spillage): S-QStowage category (IMDG): DStowage and handling (IMDG): SW1

Segregation (IMDG) : SG16, SG59, SG72

MFAG-No : 140

Air transport

: E2 PCA Excepted quantities (IATA) PCA Limited quantities (IATA) : Y540 PCA limited quantity max net quantity (IATA) : 0.5L PCA packing instructions (IATA) : 550 PCA max net quantity (IATA) : 1L CAO packing instructions (IATA) : 554 CAO max net quantity (IATA) : 5L Special provision (IATA) : A96 ERG code (IATA) : 5C

Inland waterway transport

Classification code (ADN) : OC1

Special provision (ADN) : 196, 553

Limited quantities (ADN) : 1 L

Excepted quantities (ADN) : E2

Equipment required (ADN) : PP, EP

Number of blue cones/lights (ADN) : 0

Rail transport

Classification code (RID) : OC1
Special provision (RID) : 196, 553
Limited quantities (RID) : 1L
Excepted quantities (RID) : E2

#### Safety Data Sheet

According to OSHA 29 CFR 1910.1200

Packing instructions (RID) : P504, IBC02
Special packing provisions (RID) : PP10, B5
Mixed packing provisions (RID) : MP15
Portable tank and bulk container instructions (RID) : T7

Portable tank and bulk container special provisions : TP2, TP6, TP24

(RID)

Tank codes for RID tanks (RID) : L4BV(+)

Special provisions for RID tanks (RID) : TU3, TC2, TE8, TE11, TT1

Transport category (RID) : 2
Special provisions for carriage - Loading, : CW24

unloading and handling (RID)

Colis express (express parcels) (RID) : CE6
Hazard identification number (RID) : 58

#### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

#### **SECTION 15: Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no REACH candidate substance

Contains no REACH Annex XIV substances.

Contains no substance subject to REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 concerning the export and import of hazardous chemicals.

Substance(s) are not subject to Regulation (EC) No 850/2004 of the European Parliament and of the Council of 29 April 2004 on persistent organic pollutants and amending Directive 79/117/EEC.

#### 15.1.2. National regulations

No additional information available

#### 15.2. Chemical safety assessment

No additional information available

#### **SECTION 16: Other information**

Other information

: DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.

Full text of H- and EUH-phrases:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Flam. Liq. 3	Flammable liquids Category 3
Org. Perox. D	Organic Peroxide Category D
Ox. Liq. 1	Oxidizing liquids Category 1
Skin Corr. 1A	Skin corrosion/irritation Category 1A
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H226	Flammable liquid and vapour
H242	Heating may cause a fire.

# Safety Data Sheet According to OSHA 29 CFR 1910.1200

H271	May cause fire or explosion; strong oxidizer
H302	Harmful if swallowed
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H332	Harmful if inhaled
H335	May cause respiratory irritation
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

#### SDS\_U

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.